DoP
VERSION: 1/2026

(DoP: E-106)

# Declaration of performance

## Construction Products Regulation (EU) No 305/2011

| | |
|---|---|
| **1.** Product: | Masterreflect pre-tape |
| **2.** Product Identification: | See bar code and label on packaging. |
| **3.** Intended Use: | Flexible membranes for water waterproofing, EN 13956 |
| **4.** Manufacturing Locations: | VM Building Solutions NV/SA<br>Europalaan 73<br>B-9800 Deinze |
| **5.** Representative Contact: | N.A. |
| **6.** AVCP: | 2+ |
| **7.** Notified Body (hEN): | BCCA<br>Hermeslaan 9, 1831 BE-Diegem<br>Registration No. 0749 |
| **8.** Notified Body (ETA): | N.A. |


| **9.** Declared Performance: | | | |
|---|---|---|---|
| **Essential Characteristics** | **Performance** | **Test standard** | **Harmonised technical specifications** |
| Effective Thickness | -5% to +10% | EN 1849-2 | EN 13956: 2012 |
| Reaction to Fire | E | EN 13501-1 | |
| Joint Peel Resistance (N/50mm) | ≥ 50 | EN 12316-2 | |
| Joint Shear Resistance (N/50mm) | ≥ 200 | EN 12317-2 | |
| Tensile (Breaking) Strength (N/50mm) | ≥ 400 | EN 12311-2 | |
| Elongation (%) | ≥ 15 | EN 12311-2 | |
| Tear Resistance (N) | ≥ 25 | EN 12310-1 | |
| Dimensional Stability (%) | ≤ 0,5 | EN 1107-2 | |
| Flexibility at Low Temperature (°C) | ≤ -45 | EN 495-5 | |
| UV Exposure | pass | EN 1297 | |
| Resistance to Ozone | pass | EN 1844 | |
| Resistance to Impact (method B) (Classe L) | ≥ L20 | EN 12730 | |
| Static Puncture (method B) (mm) | ≥ 2.000 | EN 12691 | |
| Hazardous substances | pass | | |

**10.** Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sammy Baron



Technical Director
VM Building Solutions NV/SA